











- allure Locking brings the versatility and natural look of Extra Wide and Rusty collections, state-of-the-art innovative LVT resilient flooring products.
- allure Locking offers the benefits of simple, no glue installation with no requirement of underlay or heavy tools, making it cheaper, quicker and cleaner to install.
- Completely waterproof, allure Locking is also warm and quiet underfoot. The product is durable and hygienic, making it suitable for retail, office, hospitality, leisure and residential purposes.
- The first Locking system to be launched in the resilient flooring industry, allure Locking has a proven track record of successfull installations and durability.
- allure Locking is produced with 100% pure virgin PVC, with all quality and health aspects under strict control.
- Completely recyclable because there are no glue residues or discontaminants, allure Locking can also be dismantled and reinstalled, making it the perfect environmentally sustainable product.















Southern Hickory White - 100211









Southern Hickory Red - 100217



Golden Oak MOcha - 96714









Smoked Oak Grey - 966104









Rustic Nutmeg - 971102



Rustic Forest - 971105











Technical Specifications

| | ALCOHOLD TO THE REAL PROPERTY OF THE PARTY O |
|--------------------------------------|--|
| allure Locking | Extra Wide |
| Thickness (mm) | 5.00 |
| Wear Layer (mm) | 0.55 |
| Utilization Class | |
| Coating | PU with Ceramic Bead (CB) |
| Embossing | True-Wood Structure |
| Bevelled | yes |
| Fiberglass | yes |
| Plank Size | 220 x 1210 mm |
| Sqm per Plank / Pack | 0.266 m ² / 1.86 m ² |
| Pallet Packing | 66.9 m2 / 36 packs |
| Planks per Pack | 7 planks |
| Net Wt/Gross Wt per Pallet | 680 kg / 730 kg |
| Impact Sound Insulation ISO 717-2 | 5 dB |
| Chemical Resistance EN 423 | High Resistance |
| Residual Indentation EN 433 | ≤ 0,08 mm |
| Dimensional Stability EN 434 | ≤ 0,08% |
| Color Fastness to Light EN 20105-B02 | ≥ 6 |
| Slip Resistance DIN 51130 | R10 |
| Watertightness EN13553 | No Penetration |
| Wear Resistance EN 660-2 | Group T |
| Antimicrobial Activity ASTM G 21-96 | Class 0 |
| Fire Rating EN ISO 9239-1 | Bfl -S1 |
| Warranty for Domestic use | 25 Years |
| Warranty for Commerical use | 10 Years |
| | |

Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. Easylock itself can be completely recycled.