



allure LOCKING

Rusty



Embossing: Honed / **Thickness:** 5.00 mm / **Wear Layer:** 0.55 mm / **Coating:** PU with Ceramic Bead (CB) /
Utilization Class: 33/42 / Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. EasyLock itself can be completely recycled.





Embossing: Honed / **Thickness:** 5.00 mm / **Wear Layer:** 0.55 mm / **Coating:** PU with Ceramic Bead (CB) /
Utilization Class: 33/42 / Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. EasyLock itself can be completely recycled.





allure LOCKING	Rusty			
Thickness (mm)	5.00	Impact Sound Insulation	ISO 717-2	5 dB
Wear Layer (mm)	0.55	Chemical Resistance	EN 423	High Resistance
Utilization Class		Residual Indentation	EN 433	≤ 0,08 mm
Coating	PU with Ceramic Bead (CB)	Dimensional Stability	EN 434	≤ 0,08%
Embossing	Honed	Color Fastness to Light	EN 20105-B02	≥ 6
Bevelled	yes	Slip Resistance	DIN 51130	R10
Fiberglass	yes	Watertightness	EN13553	No Penetration
Plank Size	220 x 1210 mm	Wear Resistance	EN 660-2	Group T
Sqm per Plank / Pack	0.266 m ² / 1.86 m ²	Antimicrobial Activity	ASTM G 21-96	Class 0
Pallet Packing	66.9 m ² / 36 packs	Fire Rating	EN ISO 9239-1	Bfl -S1
Planks per Pack	7 planks	Warranty for Domestic use		25 Years
Net Wt/Gross Wt per Pallet	680 kg / 730 kg	Warranty for Commerical use		10 Years

Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. Easylock itself can be completely recycled.

- allure Locking brings the versatility and natural look of Rusty collection, a state-of-the-art innovative LVT resilient flooring product.
- allure Locking offers the benefits of simple, no glue installation with no requirement of underlay or heavy tools, making it cheaper, quicker and cleaner to install.
- Completely waterproof, allure Locking is also warm and quiet underfoot. The product is durable and hygienic, making it suitable for retail, office, hospitality, leisure and residential purposes.
- The first Locking system to be launched in the resilient flooring industry, allure Locking has a proven track record of successful installations and durability.
- allure Locking is produced with 100% pure virgin PVC, with all quality and health aspects under strict control.
- Completely recyclable because there are no glue residues or contaminants, allure Locking can also be dismantled and reinstalled, making it the perfect environmentally sustainable product.

