




AA11 MIDNIGHT



AA02 SOAPSTONE



AA08 LEATHER



AA10 LAVA

**Specification**

Construction	:	Tufted Multi-Level Loop
Pile Content	:	100% Nylon BCF
Dyeing Method	:	Solution Dyed
Tufting Gauge	:	1/12 inch
Tufted Density	:	1,984 / Dm ²
Pile Weight	:	19 oz./sq.yd. (644 gram/sq.m.)
Pile Height	:	2.5 – 5 mm.
Primary Backing	:	Non Woven Polyester Spunbond
Secondary Backing	:	EcoSquare®, Glass Reinforced Recycled Backing
Pile Treatment	:	Stain Protection and Dry Soil Repellency
Tile Size	:	50 x 50 cm.

Performance

Overall Classification (BS EN 1307)	:	Heavy
Castor Chair Rating (BS EN 985)	:	≥2.4 Continuous use
Dimension Stability (BS EN 986)	:	≤0.15%
Static Electricity (AATCC 134)	:	≤3.0 kV, under standard test condition (70 F & 20% RH)

Color Fastness

To Light (ISO 105 B02)	:	Minimum 6 or better
To Rubbing Wet (ISO 105 – X12)	:	Minimum 4
To Rubbing Dry (ISO 105 – X12)	:	Minimum 4

Flammability

Hot Metal Nut Test (BS 4790)	:	Low radius of effects of ignition
Flame Resistance (ASTM D 2859)	:	Passes Methenamine Pill Test
Radiant Panel Test (ASTM E648)	:	≥0.45 watt/cm ² - Class I
Smoke Density (ASTM E662)	:	≤450 Dmc
Fire Classification (BS EN 13501)	:	Radiant Heat Source, Class C _{fl} – s1

Acoustic Behavior

Sound Absorption	:	EN ISO 354 and EN ISO 11654
------------------	---	-----------------------------

Indoor Air Quality

This product are certified through the Carpet & Rug Institute (CRI) Green Label Plus® certification program, as GLP1022



EcoSquare®
Glass Reinforced Recycled Backing