



PLATINUM



AVANGARD

“Happiness
by it's
nature”
2019



CLASSIC



MODERN



SILVER 5001

ARAS MEŞE

AC3 / 31. SINIF / 8 MM
192,5x1200 MM

SILVER 5002

SAKARYA MEŞE

AC3 / 31. SINIF / 8 MM
192,5x1200 MM



SILVER 5003

LİVA MEŞE

5

AC3 / 31. SINIF / 8 MM
192,5x1200 MM

KLASİK 704

ABANT MEŞE

AC3 / 31. SINIF / 8 MM
192,5 x 1200 MM

KLASİK 715

ILGAZ MEŞE

AC3 / 31. SINIF / 8 MM
192,5 x 1200 MM

KLASİK 717

RUSTİK CEVİZ

AC3 / 31. SINIF / 8 MM
192,5 x 1200 MM

MODERN 705

PRESTİJ MEŞE

3

AC4 / 32. SINIF / 8 MM

192,5x1200 MM / 4 KENARI DERZLİ



PLATINUM 2104

AMERİKAN CEVİZ

AC4 / 32. SINIF / 10 MM
190x1380 MM / 4 KENARI DERZLİ



AVANGARD 4015

TUNA MEŞE

AC4 / 32. SINIF / 10 MM
142,5x1380 MM / 4 KENARI DERZLİ

AVANGARD 4525

OTANTİK MEŞE

AC4 / 32. SINIF / 10 MM
142,5x1380 MM / 4 KENARI DERZLİ


Maintenance of your Flooring and the Details to be Considered:

- Use a vacuum cleaner or soft cordless vacuum cleaner for the daily cleaning of your floor.
- The stains and dirt can be easily cleaned with a slightly damp cloth. Make sure that you well wring out the cloth before wiping your floor.
- For cleaning, it will be enough to add liquid soap only into the cleaning water. We certainly do not recommend that you use some cleaning agents such as chemicals and alcohol for the cleaning
- For your flooring to maintain its initial beauty for many years, we recommend that you lay such materials as mats or carpets on the floor, particularly at the door entrances or in the areas with heavy traffic. It will prevent your floor from being scratched to adhere such soft materials onto the legs of your heavy furniture, which needs to be frequently moved, as felt, rubber, etc.
- Make sure that you have checked with our dealer whether the area where to be floored is suitable for flooring.
- In a space to be decorated, the laminate flooring is the last product to be installed. For installation, the installation of doors and windows and joinery, painting and crown molding works must be completed.
- Please make sure that you have read the instructions for use before starting to use your flooring.

NO	Technical Properties	Method	Performance (Standart)	Unit				
1	Thickness (t)	TS EN 13329 + A1	$\Delta t_{\text{en13329}} \leq 0,50$, $t_{\text{en13329}} - t_{\text{en13329}} \leq 0,50$	mm				
2	Width (W)		$\Delta W_{\text{en13329}} \leq 0,10$, $W_{\text{en13329}} - W_{\text{en13329}} \leq 0,20$	mm				
3	Length and width (l)		$l \leq 1500 : \Delta l \leq 0,5 \text{ mm}$, $l > 1500 : \Delta l \leq 0,3 \text{ mm/m}$	mm				
4	Length and width tolerance (q)		$q_{\text{en13329}} \leq 0,20$	mm				
5	The accuracy of the surface layer (s)		$S_{\text{en13329}} \leq 0,30$	mm / m				
6	Surface smoothness of the elements (f)		$f_{\text{en13329}} \leq \% 0,15$, $f_{\text{en13329}} \leq \% 0,20$ $f_{\text{en13329}} \leq \% 0,50$, $f_{\text{en13329}} \leq \% 1,00$	%				
7	Element spacing (O)		$O_{\text{en13329}} \leq 0,15$, $O_{\text{en13329}} \leq 0,20$	mm				
8	Height difference between elements		$h_{\text{en13329}} \leq 0,10$, $h_{\text{en13329}} \leq 0,15$	mm				
9	Surface stability	TS EN 13329 + A1 / TS EN 311	$\leq 1,00$	N/mm ²				
10	Swelling	TS EN 13329 + A1	$\leq \% 18$	%				
11	Moisture	TS EN 322	$\% 4 \leq H \leq \% 10$ $H_{\text{en13329}} - H_{\text{en13329}} \leq \% 3$	%				
12	Formaldehyde emission	TS 4894 EN 120	E1 için ≤ 8 E2 için $8 < \text{ve} \leq 30$	mg / 100gr				
13	Dimensional changes against content	TS EN 13329 + A1 / TS EN 318	$1_{\text{en13329}} \leq 9$ $W_{\text{en13329}} \leq 0,9$	mm				
14	Abrasion resistance	TS EN 13329 + A1	for AC3; ≥ 2000 for AC4; ≥ 4000	cycle				
15	Small balls against resistance	TS EN 13329+A1 / TS EN 438-2	<table><tr><td>Big Balls</td><td>Small Balls</td></tr><tr><td>$\leq 1000 \text{ mm}$ ise $\leq 15N$,</td><td>$\leq 1400 \text{ mm}$ ise $\leq 12N$ olmalı.</td></tr></table>	Big Balls	Small Balls	$\leq 1000 \text{ mm}$ ise $\leq 15N$,	$\leq 1400 \text{ mm}$ ise $\leq 12N$ olmalı.	N/mm
Big Balls	Small Balls							
$\leq 1000 \text{ mm}$ ise $\leq 15N$,	$\leq 1400 \text{ mm}$ ise $\leq 12N$ olmalı.							
16	Big balls against resistance	TS EN 13329+A1 / TS EN 438-2						
17	Resistance to staining	TS EN 438-2	5 (group 1 ve group 2) 4 (group 3)	Degree				
18	Resistance to cigarette burns	TS EN 438-2	4	Degree				
19	Resistance to effect of furniture	TS EN 425	do not harm for apparent					
20	Resistance to effect of castor chair	TS EN 424	do not change or harm appearance					
21	Appearance, surface defects	TS EN 438-2	iniquation; 1,00 mm / m ² fibers, hairs and scratch; 10 mm / m ² In case each defect occurs on the same plate, then the acceptable defects will be reduced by 50%.					
22	Static pitting	TS EN 433	$\leq 0,01$	mm				
23	Light fastness	TS EN 20105	no bad than 4.	Degree				
		TS EN ISO 105	no bad than 6.					


CLASSIC

PACK	8 PIECE
WITH	192.5 MM
LENGHT	1200 MM
THICKNESS	8.1 MM
1 PIECE	0.231 M2
1 PACK	1.85 M2
PACK-KG	15 +/- KG
1 PALLET	60 PACK
1 PALLET	480 PANEL
1 PALLET	111 M2
1 PALLET KG	845 NET / 850 GROSS
PALLET DIMENSION	1230 X 850 X 1180 MM




PLATINUM

PACK	7 PIECE
WITH	192.5 MM
LENGHT	1380 MM
THICKNESS	10 MM
1 PIECE	0.265 M2
1 PACK	1.86 M2
PACK-KG	18 +/- KG
1 PALLET	56 PACK
1 PALLET	392 PANEL
1 PALLET	104.16 M3
1 PALLET KG	985 NET / 990 GROSS
PALLET DIMENSION	1230 X 850 X 1180 MM




MODERN

PACK	8 PIECE
WITH	192.5 MM
LENGHT	1200 MM
THICKNESS	8 MM
1 PIECE	0.231 M2
1 PACK	1.85 M2
PACK-KG	15 +/- KG
1 PALLET	60 PACK
1 PALLET	480 PANEL
1 PALLET	111 M2
1 PALLET KG	845 NET / 850 GROSS
PALLET DIMENSION	1230 X 850 X 1180 MM



AVANGARD

PACK	8 PIECE
WITH	145 MM
LENGHT	1380 MM
THICKNESS	10 MM
1 PIECE	0.200 M2
1 PACK	1.6 M2
PACK-KG	16 +/- KG
1 PALLET	60 PACK
1 PALLET	480 PANEL
1 PALLET	96 M2
1 PALLET KG	905 NET / 910 GROSS
PALLET DIMENSION	1400 X 800 X 1350 MM



Suitabel for underfloor heating

Resistance to Scratch

Impact Resistance

Environmentally Friendly

Resistance to Cigarette Fire

Resistance to Furniture wheel Abrasion

Easily Cleaned and Maintained, Hygienic

Resistant to Point Strikes

Dimensional Stability

Not Affected by Stains

Resistant to UV Rays

For Office and Workplace

Suitable for Child Rooms

Formaldehyde Emission HCHO (Class)

FSC® C137016
The mark of responsible forestry

EPLF

TSE
TS EN 717-1

TSE
TS EN 13329+A1

Deutscher Akkreditierungs Rat
DAR

ISO 9001 SGS

ISO 14001 SGS

ISO 19011 SGS

ISO 13045 10001 SGS

CE

FSC®
Please ask for information

10 YEARS WARRANTY

5 YEARS WARRANTY

www.camsanparke.com