

ECOLAY+
EASIEST & STRONGEST GLUELESS LVT

SIZE & PACKING

THICKNESS	WEAR LAYER	SIZE (MM)	PCS/BOX	SQM/BOX
5mm	0.30mm	180 x 1202	10	2.16
		60 x 60	6	2.16

TEST RESULT

PRODUCT SPECIFICATION	STANDARD	ECOLAY+
Surface Treatment (NOX EPT Shield)	ISO 22196 ASTMA G21 – 15	Anti-bacterial Anti-Fungi
LEVEL OF USE	ISO 10874	0.30mm : 23 , 31
Dimensional stability	ISO 23999	<0.10%
Abrasion Group	EN 660 - 2	T
Castor Chair Resistance	ISO 4918	No damage
Slip resistance	EN 13893	DS
Fire Resistance	EN 13501-1	Bfl – s1
VOC Emissions	IAC GOLD CERTIFIED Floor score Certified	Ver Low VOC

Design Center & Office
KD Center, 355, Hyoryeong-ro,
Seocho-gu, Seoul, 06643 Korea
Tel +82-2-520-7600
Fax +82-2-598-9674

NOX Corp. | KOREA
Shinho Factory
Shinho 2nd Factory, Yedang
Enbo Factory
Godeok Factory
Bongsan Factory
Deoksan Factory
Choongnam, Korea

NOX US | USA
NOX US
P.O.Box 824
931 S. Springville Avenue
Fostoria, OH 44830
Office +01-419-701-5060
Fax +01-419-701-5058

www.noxglobal.com
info@noxglobal.com

NOX Corp.

Please visit www.noxglobal.com for the detailed installation, maintenance guides and technical information.

ECOLAY+
EASIEST & STRONGEST GLUELESS LVT

No Stick, No Click, Just Lay

ECOLAY+
EASIEST & STRONGEST GLUELESS LVT

STOCK RANGE

No stick, No Click, Just Lay

Tile Size (mm) 60x60



NLI-2130-5003



NLI-27814-5003



NLI-40901-5003

Tile Size (mm) 180x1200



NLP-5511-5003



NLP-43101-5004



NLP-43111-5005



NLP-400A3-5006



NLI-2130-5003