


Grain



Grain




**Specification according to EN 1307**


Type of manufacture	Tufted 1/10 "	ISO 2424
Aspect	Loop pile	ISO 2424
Dye method	Solution dyed	
Dimension	50 cm x 50 cm / 19,68" x 19,68"	EN ISO 24342 (20 tiles per box)
Primary backing	Polyester fleece	ISO 2424
Secondary backing	DESSO ProBase Polyver®	ISO 2424
Pile fibre composition	BCF Polyamide 6	ISO 2424
Total thickness	6.5 mm      0.3 inch	ISO 1765
Effective pile thickness	3.4 mm      0.13 inch	ISO 1766
Total mass	4050 g/m <sup>2</sup> 119.5 oz/yd <sup>2</sup>	ISO 8543
Total pile mass	620 g/m <sup>2</sup> 18.3 oz/yd <sup>2</sup>	ISO 2424
Effective pile mass	410 g/m <sup>2</sup> 12.1 oz/yd <sup>2</sup>	ISO 8543
Pile density	0.121 g/cm <sup>3</sup> 0.0044 lb/in <sup>3</sup>	ISO 8543
Number of tufts	1580 /dm <sup>2</sup> 132104 /yd <sup>2</sup>	ISO 1763
Stroll test	≤ 2,0 kV	ISO 6356
Vertical resistance	≤ 1 x 10 <sup>9</sup> Ohm	ISO 10965
Use classification	33 Commercial - heavy use	EN 1307
Dimensional stability	≤ 0,2 %	EN 986
Impact sound reduction ΔL <sub>w</sub>	27 dB	ISO 10140
Noise reduction	0.20 α <sub>w</sub>	ISO 354
Flammability	B <sub>f1</sub> - s1 (loose laid tested)	EN 13501-1
Light Reflectance Value (LRV)	See right side page per colour	BS 8493
Colour Depth (L)	See right side page per colour	CIELAB




**1908**  
L 49,83 / LRV 18,27




**9501**  
L 31,58 / LRV 6,90



**8331**  
L 24,14 / LRV 4,14



**9990**  
L 20,73 / LRV 3,18




**9506**  
L 42,94 / LRV 13,12

Grain

With ProBase™ backing      With EcoBase™ backing





EN 14041  
0493-CPR-0002

Manufactured by  
Tarkett BV  
PO Box 169  
NL-5240 AD  
Waalwijk

