



# MAZE



TILE



# MAZE




Vanilla

297




Beige

397




Red

527



Charcoal Brown

947




Black

887



Blue

757



Steel Grey

447

# MAZE



## SPECIFICATIONS

|                          |                                                        |
|--------------------------|--------------------------------------------------------|
| Construction             | VLOC                                                   |
| Product                  | MAZE                                                   |
| Pile Fiber Composition   | 100% Nylon (Polyamide 6)                               |
| Yarn Type                | BCF                                                    |
| Dye Method               | Solution Dyed                                          |
| Pile Weight              | 750 g/m <sup>2</sup>                                   |
| Number of Tufts          | 260700/m <sup>2</sup>                                  |
| Tufting Gauge            | 1/12"                                                  |
| Primary Backing          | Non-Woven                                              |
| Secondary Backing        | StableShield - 100% Vinyl                              |
| Optional Backings        | Recova-PU Cushion, EcoShield - 100%                    |
| Tile Size                | 50 cm x 50cm                                           |
| Pile Height              | 3.5 mm / 5.0 mm                                        |
| Total Tile Height        | 7.0 mm                                                 |
| Pile Treatment           | INVISTA Anti-Soil treatment, Anti-Microbial (Optional) |
| Recommended Installation | Monolithic or Quarter Turn                             |

## Performance Specifications

|                         |                                  |                                        |
|-------------------------|----------------------------------|----------------------------------------|
| Wear Classification     | Heavy Contract                   |                                        |
| VOC Emission            | ASTM D5116-06                    | <0.5 mg/m <sup>2</sup> /hour (CRI GLP) |
| Flammability            | ASTM D-2859//FF 1-70//16CFR 1630 | Pass 8/8                               |
| Critical Radiant Flux   | ASTM E648-08                     | Class 1                                |
| Static Propensity       | ISO 6356                         | 0.2 KV                                 |
| Color Fastness          | AATCC/16                         | 5/5 on Grey Scale.                     |
| Thermal Resistance      | ISO 8302                         | .04 m2/KW                              |
| Impact Sound Insulation | ISO 140-8                        | 23dB                                   |
| Sound Absorption Level  | EN ISO 11654                     | w: 0.15(H)                             |
| Soiling Propensity      | ASTM D 6540-00                   | 4                                      |
| Dimensional Stability   | EN 986                           | < 0.20%                                |
| Castor Chair Test       | DIN 54324                        | R ≥ 2.4                                |
| Smoke Density           | EN ISO 9239-1:2002               | <450                                   |

