



9555 Deep Sea



9773 Signature



9774 Silver Grey



9794 Willet



SPECIFICATION

Style	:	OXFORD
Pile Fiber Composition	:	100% Olefin (Polypropylene)
Yarn Type	:	BCF
Dye Method	:	Solution Dyed
Construction	:	Loop Pile
Total Thickness	:	7.5 mm
Pile Thickness	:	3.00 mm /4.50 mm
Pile Weight	:	725 g/m ²
Number of Tufts	:	181700 / m ²
Tufting Gauge	:	1/10"
Primary Backing	:	Non-Woven
Backing Structure	:	Stable Shield 100% Vinyl
Pile Treatment	:	INVISTA Anti - Soil treatment, Anti-Microbial (Optional)
Tile Size	:	50 cmx50cm
Package	:	20 pcs per box (5m ²)
Recommended Installation	:	Brick or Quarter Turn

PERFORMANCE SPECIFICATION

Voc Emmision	ASTM D5116-06	<0.5 mg/m ² /hour
Flammability	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
Reaction To Fire	EN ISO 9239-1:2002	Dfl-s1
Static Propensity	ISO 6356	0.2 kV
Colour Fastness	AATCC/16	5/5 on Grey Scale
Thermal Resistance	ISO 8302	.04m ² K/W
Impact Sound Insulation	ISO 140-8	ΔLw 23dB
Sound Absorption Level	EN ISO 11654	αw: 0.15(H)
Soiling Propensity	ASTM D 6540-00	4
Dimensional Stability	EN 986	< 0.20%
Castor Chair Test	DIN 54324	R ≥ 2.4



- Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of $\pm 5\%$
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies