SCAFFOLD

URBAN GRID COLLECTION


18"x 36"(45.72 x 91.44 cm)



Mannington







UrbanGrid 11212 Crosstown



UrbanGrid 13219 District



UrbanGrid 82213 Midtown



UrbanGrid 82214 Province



UrbanGrid 35216 Ward







Urban Grid Collection

Style	Scaffold (Modular)

Construction Textured Patterned Loop

Face Fiber Type 6 Nylon

Dye Method Solution

 Guage
 5/64 (50.39 per 10 cm)

 Stitches Per Inch
 9.33 (36.73 per 10 cm)

 Density
 5,305 (197.12 kg/m³)

 Pile Thickness
 0.095" (2.41 mm)

 Weight
 14 oz/yd² (475 g/m²)

 Backing Type
 Infinity® 2 Modular

Sizes 18" x 36" (45.72 x 91.44 cm)

 Colors
 8

 Pattern Repeat
 N/A

Packaging8 yd² / 16 TilesAdhesiveInfinity 2 Adhesive

Installation Method Horizontal Brick Ashlar

Testing

Dimensional Stability (Aachen Test) Passes

Electrostatic Propensity (AATCC 134) Less than 3.0 kV

Flooring Radiant Panel (ASTM E648) Passes - Class 1; ≥ 0.45 watts/cm²

Smoke Density (ASTM E662)Passes - ≤ 450Methenamine Pill Test (ASTM D2859)PassesHexapod (ASTM D5252) TARR3.5 - severe

Environmental Data

NSF/ANSI 140 Certification Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold

 Recycled Content
 Contains recycled content

 Indoor Air Quality
 CRI Green Label Plus Certified

 Product Declarations
 Third Party Verified EPD, HPD

Carbon Offset 105% Cradle to Gate (A1 - A3), visit website for more information

LEED May contribute to LEED credits:

Building Product Disclosure & Optimization - EPDs;

Building Product Disclosure & Optimization - Sourcing Raw Materials;

 $Building\ Product\ Disclosure\ \&\ Optimization\ -\ Material\ Ingredients;\ IEQc2\ -\ Low\ Emitting\ Materials$

mindful MATERIALS Visit mindful materials.com for current transparency information

Manufacturing Calhoun, GA (USA) - ISO 14001 Registered

Warranty

Limited Lifetime Wear & Backing Warranty
Limited 15-Year XGUARD® Stain Resistant Warranty
Limited 15-Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.



