



2740 Iris



2754 Sage



2777 Milfoil



2794 Currant



### SPECIFICATION

Style	:	SPARK
Pile Fiber Composition	:	100% Olefin (Polypropylene)
Yarn Type	:	BCF
Dye Method	:	Solution Dyed
Construction	:	Loop Pile
Total Thickness	:	8 mm
Pile Thickness	:	3.0 mm /5.0 mm
Pile Weight	:	780 g/m <sup>2</sup>
Number of Tufts	:	236500/ m <sup>2</sup>
Tufting Gauge	:	1/12"
Primary Backing	:	Non-Woven
Backing Structure	:	Stable Shield 100% Vinyl
Pile Treatment	:	INVISTA Anti - Soil treatment, Anti-Microbial (Optional)
Tile Size	:	50 cmx50cm
Package	:	20 pcs per box (5m <sup>2</sup> )
Recommended Installation	:	Brick or Quarter Turn

### PERFORMANCE SPECIFICATION

Voc Emmission	ASTM D5116-06	<0.5 mg/m <sup>2</sup> /hour
Flammability	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
Reaction To Fire	EN ISO 9239-1:2002	Dfl-s1
Static Propensity	ISO 6356	0.2 kV
Colour Fastness	AATCC/16	5/5 on Grey Scale
Thermal Resistance	ISO 8302	.04m <sup>2</sup> K/W
Impact Sound Insulation	ISO 140-8	ΔLw 23dB
Sound Absorption Level	EN ISO 11654	aw: 0.15(H)
Soiling Propensity	ASTM D 6540-00	4
Dimensional Stability	EN 986	< 0.20%
Castor Chair Test	DIN 54324	R ≥ 2.4



- Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies