

# Ultimo

LUXURY VINYL TILES



100% Made In Belgium







Summer Oak 24935

### Summer Oak



24935



24244

-  **Click Unidrop®**  
Available in:  
19,1 x 131,6 cm
-  **4 sided bevel**
-  **Thickness**  
4,5 mm
-  **Wear layer**  
0,55 mm





Paris Oak 22230

Paris Oak



22230


Chapman Oak



24239

 **Click Unidrop®**  
Available in:  
19,1 x 131,6 cm

 **4 sided bevel**

 **Thickness**  
4,5 mm

 **Wear layer**  
0,55 mm



# Technical specifications

## TECHNICAL INFO OF ULTIMO

Dryback      Click

### PRODUCT INFORMATION

Level of use	EN ISO 10874	23 - 33 - 41	23 - 33
Total thickness	EN ISO 24346	2.5 mm	4.5 mm
Wear layer	EN ISO 24340	0.55 mm	0.55 mm
Wear Layer PUR treatment		Superguard Pro®	Superguard Pro®
Total weight g/m <sup>2</sup>	EN ISO 23997	4105.5	7805.5

### SIZE & PACKING

Planks	EN ISO 24342	19.6 x 132 cm	19.1 x 131.6 cm
Tiles	EN ISO 24342	32.9 x 65.9 cm	32.4 x 65.5 cm
Box planks		3.62 m <sup>2</sup> 14 pcs/box	1.76 m <sup>2</sup> 7 pcs/box
Box tiles		3.47 m <sup>2</sup> 16 pcs/box	1.49 m <sup>2</sup> 7 pcs/box

### TEST RESULTS

Inflammability	EN 13501	Bfl-S1	
Abrasion group	EN ISO 660-2	Class T	
Scratch resistance	EN 16094	≤MSR-A2, ≤MSR-B2	
Squareness	EN ISO 24342	± 0.35 mm	
Straightness	EN ISO 24342b	± 0.35 mm	
Slip resistance	EN 13893	DS	
Slip restraint	DIN 51130	R10	
Residual indentation	EN ISO 24343-1	Norm: ≤ 0.10 mm Average result: 0.03 mm	
Furniture leg resistance	EN ISO 16581	No cracks, no damage	
Curling	EN ISO 23999	± 1.21 mm	± 1.11 mm
Dimensional stability	EN ISO 20326	Norm: ± 1.0251% Average result: ± 1.0051%	Norm: ± 1.0151% Average result: ± 1.0051%
Thermal resistance R	EN 12667	0.0100 m <sup>2</sup> K/W	0.0159 m <sup>2</sup> K/W
Acoustic insulation	EN ISO 717-2	4 dB	
Acoustic insulation + Xtrafloor Acoustic Comfort		19 dB	
Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination	
Stain resistance	EN ISO 26987	Very good	
Light fastness	EN ISO 105-B02	≥ 6	
Underfloor heating and cooling	EN 12524	Suitable, max 27°C	
Maximum allowed ambient and surface temperature		45° C	
Warranty (year)		20 Residential - 10 Commercial	



The warranty covers manufacturing defects and premature wear in the event of normal use.

