



VINTEC -Mono is fully flexible, stable and elegant PVC Flooring with heavy duty wear layer on top providing extra protection and wear resistance making it suitable for high traffic areas

Mono – 200 SERIES




Commercial



Health Care




Education



2 MM
1.5 MM
1 MM



300 x 300 MM
600 x 600 MM



2mtr WIDTH



TECHNICAL DATA

Application		Technical Performances	
	Education		Dimensional Stability $\leq 0.40\%$
	Healthcare & Wet Area		Residual Indentation $\leq 0.10\text{ mm}$
	Residential		Castor Chair Continuous Use Suitable
	Office Retail and Hospitality		Light Fastness ≥ 6
	Transport		Flexibility Passes
Classification			Resistance to Chemicals Good resistance
	Commercial / Residential Use 33		Slip Resistance R 9
	Industrial Use 42		Fungi & Bacterial Resistance Optional
	Abrasion Resistance Group T		Electrical Resistance
Technical Characteristics			Sound absorption 5 dB
	Total Thickness 2.0 +/- 0.130 mm		Under Floor Heating Yes
	Roll Width 2000 mm		Reaction to Fire B fl-s 1
	Roll Length $\pm 15\text{ mtr.}$		Body Voltage $\leq 2\text{ kv}$
	Total Weight 3.5 kg/m ²		Thermal Conductivity 0.25W/m-K

APPLICATION:

Suitable for heavy duty commercial areas like porta cabins, prefabricated buildings, Shops, Offices, Hospitals and Schools.

INSTALLATION:

- Ensure sub floors are structurally sound, clean, smooth and dry
- Use Vinyl based Adhesive for laying

MAINTANENCE:

- Clean the surface daily with damp mop and weekly with mild soap solution.
- Use coir brush or fine steel wool No.000 soaked in warm soap solution to clean effected area.
- Do not throw lighted cigarette buffs or match sticks on the floor
- Use water to clean chemical spilling

