



SVX1517

Vancouver




Specifications

Construction	level loop
Fiber	100% Nylon 6
Dye Method	Solution Dyed
Gauge	1/10"
Stitches	15per inch
Pile Weight	16oz/yd ² (550gms/m ²)
Pile Height	3.5mm±0.5mm
Total thickness	6.5mm±0.5mm
Backing	PVC with fiberglass
Tile Size	50cm x 50cm

Performance

Flooring Radiant Panel:	ASTME 648-04
Dimensional Stability:	ASTMD 7570
Smoke Density:	ASTME 662
Electrostatic Propensity:	AATCC 134
Tuft Bind of Pile:	ASTM D 1335
Accelerated Soiling of Pile Yarn:	ASTM D 6540
Colorfastness to Light:	AATCC 16
Colorfastness to Sea Water:	AATCC 106
Colorfastness to Crocking:	AATCC 165
Stain resistance:	AATCC 175
Losse laid hot metal nut test:	BS 4790
Static load limit:	BS 4939/ ISO 3416
Edge Ravel resistance:	ASTMD 7267
Cleaning:	AATCC 138

Installation Method



Warranties

10 years limited warranty:
 No more than 10% face yarn loss by weight under normal use
 Limited static warranty
 Limited delamination warranty under normal use.









