






Whitehorse 02



Whitehorse 07



Whitehorse 08



Whitehorse 09



Whitehorse 11



Whitehorse

Specifications

Construction:	multi-level loop
Fiber:	Universal Nylon 66
Dye Method:	Solution dyed
Gauge:	1/12"
Stitches:	10 per inch
Pile Weight:	20 OZ/yd ² (680 gms/m ²)
Pile Height:	4mm ± 0.5mm
Total Thickness:	10mm ± 0.5mm
Backing:	Mix- bac
Tile Size:	50cm x 50cm

Performance

Flammability:	Passes (ASTM E648 / FF 1-70 (8/8))
Smoke Density:	Passes (ASTM E662)
Static Propensity:	≤ 3.0 kV (AATCC 134)
Soil & Stain Protection:	Excellent Soil Resistance
Colour Fastness to Light:	5 (AATCC- 16E)
Colour Fastness to Crocking:	5 (AATCC- 165)
Colour Fastness to Ozone:	5 (AATCC- 129)
Dimensional Stability:	<0.2% (AACHEN)
Dynamic Crush:	Negligible Impact or no change
Delamination Strength:	Excellent (No Separation)

Warranties

10 years limited warranty.
No more than 10% face yarn loss by weight under normal use.
Limited static warranty.
Limited delamination warranty under normal use.